



Made in America



FEATURES:

- Used for kitting and to help organize the workstation
- Durable conductive styrene
- Die-cut drop-in covers available separately
- Reusable, ensuring best value
- Great container for Kanban
- Made in America

SPECIFICATIONS:

| Property | Typical Value | ASTM |
|--------------------------|----------------------|-------|
| Specific Gravity | 1.09 | D-792 |
| Tensile Strength | 4,200 psi | D-638 |
| Tensile Elongation | 40% | D-638 |
| Flexural Modulus | 220,000 psi | D-790 |
| Flexural Strength | 6,700 psi | D-790 |
| Total/Free Sulfur | <0.15% / <0.004% | |
| Chlorides | <0.3 PPM | |
| Outgassing & Corrosivity | Low | |
| 5KV Decay Time | <0.01 sec @ 10% RH | |
| Surface Resistance | 10 ⁴ Ohms | |

| Item | Size (inches) | Cell Size (inches) | # of Cells |
|--------------|----------------------------|-----------------------|------------|
| 39206 | 10-1/2 x 8-3/4 x 1-1/2 | 2 x 1-7/8 x 1 | 12 |
| 39201 | 14-1/2 x 10-1/8 x 1-7/8 | 3-1/2 x 2-3/4 x 1-1/4 | 9 |
| 39202 | 14-3/8 x 10-1/8 x 1-3/4 | 3 x 3 x 1-1/4 | 12 |
| 39203 | Lid for Kitting Tray 39206 | | |
| 39204 | Lid for Kitting Tray 39201 | | |
| 39205 | Lid for Kitting Tray 39202 | | |

CONDUCTIVE KITTING TRAYS

PROTEKTIVE PAK

PROTEKTIVE PAK
13520 MONTE VISTA AVENUE, CHINO, CA 91710
PHONE (909) 627-2578, FAX (909) 363-7331
ProtektivePak.com

DRAWING NUMBER
39200

DATE:
September
2008